





FLEXIBLE DISK SYSTEM UNITAND SLIDE KITASSEMBLY


XPN. 100820 .












































U

	REVISIONS	
LTR	DESCRIPTION	APPROVED
_	PROTOTYPE	01-12-1
2	PER ENGR INPUT	5-18-77
4	PRODUCTION RELEASE	5-22-77
Ø	REYISED PER ECN NO.BID	728-77


⋖


NOTES: UNLESS OTHERWISE SPECIFIED


- I. RESISTORS ARE IN OHMS ±5%,1/4W
- 2. LAST USED; C55, R2
- 3. IC DEVICE TYPE LSXX=74L5XX
- 4. FOR IC POWER 4 GND PINS SEE CHART
- S APPLIES TO ASSEMBLIES USING P.C BOARD P/N 106035 REV I
- A VAR 2 E O O O I N/A DRAOB. 39 DNIEU 2318M322A OT 23199A
- DELETE ON ASSEMBLIES USING P.C.BOARD P/N 106035 REV A


1. C.	VOLTAGE REFER	ENCE		
	LOCATION	+ 5	GND	
7416	C 4	14	7	
L\$00	A14	14	7	
LSO2	AIZ. BI3 5	14	7	
L\$08	814	14	7	
L\$ 74	A13	14	7	
L\$138	A7,A8	16	8	
L\$173	A6.9-11,86,83-1(87,812)7	16	8	
8837	C3	16	8	
8838	Ca-10, C7 7	16	8	
93448	B1-5,A1-5	45	21	
LS 32	C55] B16 6]	14	7	


1200 A ...
T ASSY, USED OW

















NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL RESISTORS IN OHMS VAW, 5%.

2. I.C DEVICE TYPE LSXX = 74LSXX SKXX = 74SXX

10 V	フレイ	460	e refer	ENC	€
DEVICE	VLC	GUD	DEVICE	Vcc	GND
L500	14	7	5K387	16	8
LS02	14	7	7410	14	7
L504	14	7	7417	14	7
LSOB	14	7	F9401	14	7
1532	14	7	DM9602	16	8
L574	14	7	LS151	16	8
L585	16	8	L5164	14	7
LSEG	14	7	L5193	iLa	8
LS109	10	8	5K124	15,160	8,9
15132	14	7			
L5138	10	8			
LS153	160	9			
LS157	و١١	8			
しらしろ	10	8			
L5173	10	છ			
L5194A	10	8			
L5241	20	10			
L5273	20	10			

	LTR	<u> </u>	DESCR
	8	PROD	RELEASE
+24V +24V	L	<u> </u>	<del></del>
,,,			
1K } 1K 12W 12W 12W 12W			
+24V RC7 RC8			
2 1 8, IK Q20			
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
1K (5.1V) 3 - 420 826 20 2222A			
cezo =	- +5.	W	
1 269 2 1			•
-5V IK T 35V			
5.1K \			4
ا ا ا			
Lb 20 1			
5 + 14	17		•
1 1 1 1 W			
-5v + 35v c92			,
+24V +12V			
CZ21			
1N759 (12V)			
• •	,		
alalog power supply			

REF DESIGNATION

	1
LAST USED	NOT USED
C103	C4,C5,C6
R79	
CZ21 Q20 TP8	

			TOLERANCES I OTHERWISE S DEC ,XX DEC ,XXX ANGLES		100 See June June June June June			,
			APPROVALS	DATE	E TITLE PERSONALITY MODULE			
			DANWYS.V. 12-76 FLEXIBLE DISK DRIVE				-	
	*		CHECKED		SCALE SIZE DRAWING NO.			
1	106041	12004	^		JUONE	<u> </u>	105090	В
	NEXT ASSY.	USED ON			DO NO	T SCALE	DRAWING SHEET 1 OF	14


REVISIONS


DESCRIPTION


M XE OOIC KLINGLER VELLUM 1021-10


2


3






























BOSM WE BOTT KINDLES VELLING 1021-10

DO NOT SCALE DRAWING SHEET 12 OF 14



TOTAL YE MAIF KINGLER VELLUM 1021-10

DELETE THIS SHEET FOR CONFIGURATION -01,-03

TOLERANCES IN OTHERWISE SE DEC .XXX DEC .XXX ANGLES		AEBEC PRETAME PROCUPORATED							
APPROVALS	DATE	TITLE	TITLE PERSONALITY MODULE						
DRAWN S.V.	12-76	Fl	FLEXIBLE DISK DRIVE						
CHECKED		SCALE	SIZE	DRAWING I		-	REV.		
APP		NONE	ر	1000	040		0		
		DO NOT SCALE DRAWING SHEET 13 OF 14							

3

•

4

